

PC-1200 FG DEFOAMER

SILICONE DEFOAMER

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). Not a dangerous substance or mixture according to the Globally Harmonized System (GHS).

Recommended First Aid: **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF ON SKIN (or hair):** Remove contaminated clothing. Rinse skin thoroughly with plenty of water. **IF SWALLOWED:** Do not induce vomiting. Have a conscious victim drink water to dilute. Never give anything by mouth to an unconscious person. **IF INHALED:** Remove to fresh air.

Storage: Do not store near heat. Freezing will not change the performance of PC-1200 but may cause difficulty in handling due to high viscosity. It is recommended that PC-1200 be used within 2 years of manufacture. Beyond 2 years, the product should be tested prior to use.

Read SDS before using this product.

PC-1200 FG Defoamer is a 100% silicone compound with a 350 centistokes viscosity and all its components are in compliance with FDA regulation 21 CFR 173.340 (a)(2) and it is limited by that regulation to a maximum usage of 10 ppm in food for most uses. Consult this regulation for situations where the use limitation may be different.

DIRECTIONS FOR USE: PC-1200 is permitted in foods at a maximum of 10 ppm. It may be effective at much lower concentrations. Start with 10 ppm and reduce antifoam levels until you reach your optimal level of foam control. PC-1200 is not permitted in milk.

Target ppm	Gallons to be treated	PC-1200 to add (fluid ounces)
3	1,000	0.4
6	1,000	0.8
9	1,000	1.1

SAMPLE

Safe Foods Chemical Innovations
1501 E 8th Street
North Little Rock, AR 72114
501-758-8500

CHEMTREC EMERGENCY PHONE 1-800-424-9300

HEALTH	0
FLAMMABILITY	1
REACTIVITY	0
PPE	A



NET CONTENTS: 441 POUNDS

FOR INDUSTRIAL USE ONLY
NOT FOR RETAIL SALE ID #30555

BATCH: